D⊌'€:

Wednesday, 29/10/2008 4:19:26 PM

Úser:

Julie Dawson

Process Sheet

Customer

: CU-DAR001 Dart Helicopters Services

Job Number **Estimate Number** : 43076

: 12426

P.O. Number This Issue

: 29/10/2008

: NC Prsht Rev. First Issue

: // : 27333

S.O. No. :

Type : PURCHASED PARTS **Part Number**

Drawing Name

: D2006001

: PLACARD

: D2006 **Drawing Number**

: N/A **Project Number** : N/A **Drawing Revision**

Material

Due Date : 11/11/2008

Qty:

10 Um: Each

Written By

Previous Run

Checked & Approved By

Comment

: Est Rev:A New Issue 06-05-05 JLM

Additional Product

Job Number:



Seq. #:

1.0

Machine Or Operation:

Description:

PG

PURCHASING



Comment: PURCHASING

Fabricate as per Dwg D2006

Possible Supplier: Studio Lettrage Material release note is required

(208/10/30

Tio

2.0

D2006001P

Ident Plate- 206 Heater



Comment: Qty.:

1.0000 Each(s)/Unit Total: 10.0000 Each(s)



3.0

PACKAGING 1

PLACARD

PACKAGING RESOURCE #1



Comment: PACKAGING RESOURCE #1

Recieive & Inspect for Transit Damage Ensure Material Release Note is attached

DIMENSIONAL



4.0

QC6

Comment: DIMENSIONAL CHECK

5.0

PACKAGING 1

PACKAGING RESOURCE #1





Comment: PACKAGING RESOURCE #1

Identify and Stock

Location:



N/O:		WORK ORDER	CHANGES				
DATE STEP	PF	OCEDURE CHANGE	Ву	Date	Qty	Approval Chief Eng / Prod Mgr	Approval QC Inspector
						<u></u>	
						<i>Y</i>	
Part No:	PAR #:	Fault Category:	NCR: Yes	No DQ	A :	Date: _	
Resolu	ıtion:	Disposition:	QA: N/C (Closed:		Date: _	· · · · · · · · · · · · · · · · · · ·

NCR:		WORK ORDER NON-CONFORMANCE (NCR)								
	Description of NC		Corrective Action Section B	<u></u>	Verification	Approval	Approval			
DATE	STEP	Description of NC Section A	Initial Chief Eng	Action Description Chief Eng	Sign & Date	Section C	Chief Eng	QC Inspector		
								-		
							:			

NOTE: Date & initial all entries

Date: User: Wednesday, 29/10/2008 4:19:26 PM

Julie Dawson

Process Sheet

Customer: CU-DAR001 Dart Helicopters Services

Drawing Name: PLACARD

Job Number: 43076

Part Number: D2006001

Job Number:



Seq. #:

Machine Or Operation:

Description:

6.0

QC21

FINAL INSPECTION/W/O RELEASE





mr 08-11-10

Comment: FINAL INSPECTION/W/O RELEASE

Job Completion



Dart Aeı	rospace	Ltd							
W/O:			WO	RK ORDER CHANGE	S				
DATE	STEP	PRO	CEDURE CHAN	NGE	Ву	Date	Qty	Approval Chief Eng / Prod Mgr	Approval QC Inspector
Part No	:	PAR #:	Fault Cateo	jory:	NCR: Yes	No DQA	۸:	Date: _	
	R	esolution:	Disposition: C		QA: N/C Closed:			Date: _	
NCR:		V	VORK ORDE	ER NON-CONFORMA	NCE (NCF	R)			
		Description of NC	Corrective Action S		n B	Verific	ation	Approval	Approval
DATE	STEP	Section A	Initial Chief Eng	Action Description Chief Eng	Sign 8 Date	Section		Chief Eng	QC Inspector
i	1							1	

Description of N		Description of NC	Corrective Action Section 5			│ Verification │ Approval		Annroval	
DATE	STEP	Section A	Initial Chief Eng	Action Description Chief Eng	Sign & Date	Section C	Chief Eng	Approval QC Inspector	
						!			

NOTE: Date & initial all entries

3/4 FLOOR HEATER 3 TOT INCREASE <20°c WINDSHIELD HTR.

SHOP COPY

RETURN TO

ENGINEERING:

UNCONTROLLED COPY



WHITE LETTERS ON BLACK VINYL.

	D2006-	2001	6.	ACAR				
OTY, REQUIRED	PARTNO.	ITEM		ESCRIPTION		MATERIAL	SPEC./V	ENDOR
APPROVAL	CONTRACT NO.	. ,	DATE	de la constantina		ACCESS	ORIES I	NC
	BRADLE DESIGN BRADLE STRESS			me				
	CHECKED			*20G	DWG NO.	DZC	ACARI OOG	AEV.
	CLEAN			İ	SCALE	1:1	SHT \ OF \	1



210 MAIN W.,

HAWKESBURY, ONT. K6A 2H6

Tel.: 613 632-2001 Fax: 613 632-9491

www.studiolettrage.com

INVOICE / FACTURE

11258

No.:

11 1

11/06/2008

DATE:

1 of 1

Re: PAGE No. 6032

VENDU À: SOLD TO:

> Dart Aerospace Ltd 1270 Aberdeen Hawkesbury, Ontario K6A 1K7

LIVRÉ À: SHIPPED TO:

Dart Aerospace Ltd

Hawkesbury, Ontario

ITEM ARTICLE	QTY QYÉ	UNIT UNITÉ	DESCRIPTION	GST TPS	PST TVP	UNIT PRICE PRIX UNITÉ	AMOUNT MONTANT
		10 ~	D2006001P white on black Printing set up	G E		2.50 50.00	50.00 50.00
	,	Pesfule	E - GST @ 5% G - GST @ 5%; PST @ 8% GST PST Exempt: #6122-5207				3.75
		,	•				
			•				
			•				
) i i	
	Λ						
Studio de Lettre PO 7492 Sold By:	nge/Gst	#869034678RP001				TOTAL	78.75

Product Bulletin 8522

3M

Release F, Effective January 2003 Black bar in margin indicates a change

Scotchcal [™] Opaque Imaging Media 8522

Description

This media is specially formulated to dry quickly after printing. Production of outdoor weatherable and long-term indoor durable graphics is now easier than ever. Its changeable adhesive allows easy removal for up to one year.

Advantages

- Optimized for use with selected Epson Stylus Proprinters and Epson Archival inks.
- Optimized for use with selected HP DesignJet Printers and HP DesignJet Ink System UV or HP83UV Color Ink System
- For making opaque, laminated graphics that are outdoor weatherable and long-term indoor durable
- Media
 - For opaque (reflective) graphics
 - Changeable, easy to remove from warranted substrates up to 1 year later
 - Dries quickly after printing so the overlaminate can be applied almost immediately
 - Low slippage paper liner for superior tiling
- Overlaminates:
 - Provide additional UV (ultraviolet) and physical protection for making weatherable finished graphics
 - Available in luster and matte gloss
 - Adhesive allows for heat-assisted or cold-temperature lamination

Applications and Uses

3M™ Scotchcal™ Changeable Opaque Imaging Media 8522 is intended only for ink jet printing and for use with the listed Compatible Products and Equipment and the following applications. Any other application is NOT warranted by 3M or covered by the worldwide 3M™ MCS™ Warranty unless 3M gives its prior written approval for the application.

- First surface images (the image is on top of the film) for opaque posters and signs, including:
 - Graphics for vans, personal vehicles, trucks and buses
 - Novelty posters
 - Retail and point-of-purchase displays
 - Information graphics such as maps and directories
 - Entertainment promotions in museums, zoos, parks, theatres, sports venues
 - Education and presentation graphics

- Legal and courtroom exhibits
- For flat or simple curved surfaces, with or without rivets, used in vertical (± 10°) applications

Limitations of End Uses

The following uses and applications are specifically NOT warranted.

- Fleet applications in areas that use salt for winter road maintenance
- Application to non-warranted substrates, including wallboard
- Applications subjected to gasoline vapors or spills
- Application to corrugated or highly irregular surfaces or sharply raised areas
- Graphics applied to stainless steel, including stainless steel vehicles
- On flat surfaces with rivets, tenting of 4 to 10 mm around rivets may be expected; rivets may be cut around to eliminate tenting.

Note: Standard ink jet technology is water based. Water-based chemistry is susceptible to the extremes of heat and humidity. This is a factor in most product constructions on the market. Read the Fabrication. Shelf Life and Storage sections in this bulletin. Staying in the middle of these ranges always provides optimum performance.

Compatible Products and Equipment

Thermal Ink Jet Printing Systems

- Epson Stylus Pro 9500, Stylus Pro 10000 printer
 - Epson Archival Inks
- Epson Stylus Pro 10600 printer
 - Epson Archival Inks
- HP DesignJet Printers 2000 and 3000 series
 - HP DesignJet Ink System UV (pigment-based ink)
- HP DesignJet Printers 5000 series
 - HP83UV Color Ink System

Overlaminates (required)

- 3M[™] Luster Overlaminate 8519 (semi-gloss)
- 3M[™] Matte Overlaminate 8520

Note: For the full product names of the 3M products listed on this page, please see page 1.

Warranted Substrates

Media 8522 is warranted for use on the following rigid substrates.

Some substrates may "out-gas", resulting in tiny bubbles throughout the surface of the graphic. For maximum performance, be sure the substrate you select is properly cleaned and prepared as recommended by the manufacturer. See Instruction Bulletin 5.1 for additional information.

- Alodine (anodized aluminum)
- Automotive panels (automotive painted steel)
- Fruehauf (painted aluminum)
- FRP (fiberglass reinforced plywood)
- Glass
- Imron® (polyurethane-painted metal panel)
- Acrylic
- Sintra * board

Test and Approve Non-warranted Substrates Before Use

Media 8522 is not warranted for any substrate other than those listed above. If you want to use it for other substrates 3M recommends that you test and approve the media for both adhesion and removal characteristics.

Characteristics

Characteristic	Description
Media	7 mil, white, opaque graphic film
Liner	Low-slippage, lay flat paper
Adhesive	Changeable, pressure sensitive
Thickness (media and adhesive)	7.5 to 8 mil (nominal)
Application substrates	See Warranted Substrates, above
Application surfaces	Flat or simple curved surfaces, with or without rivets, used in vertical (± 10°) applications (no corrugations)
Application temperature range	28° to 110°F (-2° to 43°C) (air and surface)
Roll sizes	36" x 45 feet (914 mm x 13.5 m) 54" x 45 feet (1372 mm x 13.5 m)

How to Become a 3M Ink Jet Registered Fabricator

Only 3M Thermal Ink Jet Registered Fabricators are eligible to offer 3M MCS warranted graphics. In order to become certified, a fabricator must complete the requirements as specified in the 3M Ink Jet Graphics Registered Fabricator Reference Manual located on the 3M website at www. scotchprint.com

Effective Performance Life

To obtain the warranty given below, the graphics must be made according to 3M's recommendations which are detailed in the Warranty and Limited Remedies on page 3. Also see the section, Removability.

Warranted Durability

Media 8522 with	Epson Pr	inters	HP Printe	ers
Overlaminate 8519 or 8520	Outdoor	Indoor	Outdoor	indoor
Applied to Warranted Substrates	2 years	5 years	3 years	5 years

Removability

Imaging media 8522 is removable from warranted substrates for I year without the aid of chemical strippers or accessories. Refer to Instruction Bulletin 4.23 for additional information.

Fabrication

Graphics must be made according to 3M's recommendations which are detailed in the Warranty and Limited Remedies on page 3.

See Instruction Bulletin 4.23 for detailed fabrication, printing and mounting information.

Graphic Construction Options

Opaque (Reflective) Graphics

Opaque graphics made with imaging media 8522 require an overlaminate and an opaque substrate.

Viewer/Light Source	
	Overlaminate 8519, 8520 Adhesive on bottom
	Imaging Media 8522 Image on top; adhesive on botton
	Opaque Substrate

Note: For the full product names of the 3M products listed on this page, please see page 1.

Shelf Life and Storage

- 3M * Scotchcal * Changeable Opaque Imaging Media 8522 has a shelf life of one year.
- Storage conditions (new and partially used rolls). For optimum performance, use the middle of these ranges:
 - Original packaging, including plastic wrap
 - Relative humidity of 20% to 80%
 - Temperature of 33° to 104°F (0° to 40°C)
 - Away from direct sunlight
- Do not stack unprotected rolls or lay sharp or heavy objects on them.

Health and Safety

When handling any chemical products, read the manufacturers' container labels and the Material Safety Data Sheets (MSDS) for important health, safety and environmental information.

To obtain MSDS sheets for 3M products:

- By fax, call 1-800-364-0768 in the US and Canada or 1-650-556-8417 for all other locations.
- Electronically, visit us at http://www.3M.com/msds.
- By mail, or in case of an emergency, call 1-800-364-3577 or 1-651-737-6501.

When using any equipment, always follow the manufacturers' instructions for safe operation.

Warranty and Limited Remedies

3M ** MCS ** Warranty for Graphics Produced on HP DesignJet Printers and Epson Stylus Pro Printers

The following is made in lieu of all other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose: We warrant graphics produced by a 3M Ink Jet Registered Fabricator made with imaging media 8522, printed on an approved HP thermal ink jet printer according to HP's recommendations or Epson Stylus Pro printer according to Epson's recommendations, overlaminated with 8519 or 8520, and applied to a Warranted Substrate according to 3M's recommendations. These

graphics are covered against failure caused by ultraviolet light, temperature extremes, pollution, and other elements.

If a graphic fails to perform in accordance with 3M product specifications within this time frame, 3M will replace the materials at no charge. These remedies are exclusive. In no case shall 3M be liable for any direct, indirect, or consequential damages, including any labor charges.

3M Related Literature

Listed below is related 3M technical literature that may be of interest. You may view and print these Bulletins from our Web site at www.scotchprint.com, or order them via our Faxon-Demand (FOD) system. Call one of these phone numbers to order the desired bulletins, and specify the FOD document number provided in the chart.

United States or Canada: 1-800-364-0768

International: 1-651-732-6506

Subject	Bulletin No.	FOD No.
Product Bulletins		140.
3M [™] Scotchcal [™] Overlaminate 8519 and 8520	8519/8520	4524
Instruction Bulletins		
Making thermal ink jet graphics	4.23	
Application, substrate selection, preparation and substrate-specific application techniques	5.1	7001
Warrantios		·
Worldwide 3M " MCS " Warranty Packet includes all Commercial Graphics MCS Warr	President	9503
Worldwide 3M ™ MCS ™ Warranty Overvie	w-Folder	9504

3M, Scotchcal and MCS are trademarks of 3M. Epson and Stylus Pro are trademarks of Epson. HP and DesignJet are tradenames of Hewlett Packard. Sintra is a trademark of Swiss Aluminum Ltd. Imron is a registered trademark of DuPont in the United States

Bulletin Change Summary

The Epson Stylus Pro Printers 9500, 10000 10600, and Epson Archival Inks have been added to this bulletin. Additional changes resulting from this addition are marked with black bars in the margin.

3M

Commercial Graphics Division 3M Center, Building 220-6W-06 PO Box 33220 St. Paul, MN 55133-3220 USA General Info. 1-800-374-6772 Technical Info. 1-800-328-3908 Fax 1-651-736-4233 Fax-on-Demand 1-800-364-0768 US/Canada or 1-651-732-6506 International

Fax-on-Demand document: 4506 www.scotchprint.com

3M Canada P.O. Box 5757 London, Ontario Canada N6A 4T1 1-800-265-1840 Fax 519-452-6245

3M México, S.A. de C.V. Av. Santa Fe No. 55 Col. Santa Fe, Del. Alvaro Obregón México, D.F. 01210 52-55-52-70-04-00 Fax 52-55-52-70-22-77

3M Puerto Rico, Inc. Puerto Rico Industrial Park P.O. Box 100 Carolina, PR (0986-0100 787-620-3000 Fax 787-750-3035

9/3M 2003. All rights reserved. Product Bulletin 8522 - 3